



AD-R169 816 COMPUTER PROGRAMS FOR ELECTROMAGNETIC SCATTERING FROM A 1/1
SLOTTED TN CYLIND. (U) SYRACUSE UNIV NY DEPT OF
ELECTRICAL AND COMPUTER ENGINEERING. J R MAUTZ ET AL.
UNCLASSIFIED NOV 85 SYRUP/DECE/TR-85/5 ARO-21378.5-EL F/G 20/3 NL





MICROCOM

SYRU/DECE/TR-85/5

COMPUTER PROGRAMS FOR
ELECTROMAGNETIC SCATTERING FROM A SLOTTED TM CYLINDRICAL
CONDUCTOR BY THE PSEUDO-IMAGE METHOD

AD-A169 016

Interim Technical Report No. 4

by
Joseph R. Mautz
Roger F. Harrington

November 1985

Department of
Electrical and Computer Engineering
Syracuse University
Syracuse, New York 13210

Contract No. DAAG29-84-K-0078

Approved for public release; distribution unlimited

Reproduction in whole or in part permitted for any
purpose of the United States Government

Prepared for

ARMY RESEARCH OFFICE
RESEARCH TRIANGLE PARK
NORTH CAROLINA 27709

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S-N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. ABSTRACT (Continue)

plete circular cylindrical shell and the TM plane wave propagates perpendicular to the plane of the gap. To enable the user to verify that they are running correctly, both programs are provided with sample input and output data.

| | |
|--------------------|-------------------------------------|
| Accession For | |
| NTIS CRA&I | <input checked="" type="checkbox"/> |
| DTIC TAB | <input type="checkbox"/> |
| Unpublished | <input type="checkbox"/> |
| Justification | |
| By | |
| Distribution / | |
| Availability Codes | |
| Dist | or J-1 |
| A-1 | |



CONTENTS

| | Page |
|--|------|
| I. INTRODUCTION----- | 1 |
| II. THE SUBROUTINE BES----- | 2 |
| III. THE SUBROUTINES DECOMP AND SOLVE----- | 8 |
| IV. THE MAIN PROGRAM FOR THE METHODS OF SOLUTION WITH AND WITHOUT PSEUDO-IMAGE----- | 11 |
| V. THE SUBROUTINE BESJ1----- | 33 |
| VI. THE SUBROUTINE BESJY----- | 35 |
| VII. THE MAIN PROGRAM FOR THE FOURIER SERIES METHOD OF SOLUTION----- | 38 |
| REFERENCES----- | 48 |

I. INTRODUCTION

Two methods for calculating electromagnetic plane wave scattering from a perfectly conducting TM cylindrical surface with a narrow but infinitely long slot were described in [1]. These two methods are the method of solution with pseudo-image and the method of solution without pseudo-image. A Fourier series method of solution for calculating the scattering of an electromagnetic plane wave normally incident on a narrow but infinitely long slot in a perfectly conducting TM circular cylindrical surface was also described in [1]. In what follows, two computer programs are described and listed, one that implements the methods of solution with and without pseudo-image, and one that implements the Fourier series method of solution.

The computer program for the methods of solution with and without pseudo-image consists of a main program and the subroutines BES, DECOMP, and SOLVE. The subroutine BES is described and listed in Section II, the subroutines DECOMP and SOLVE in Section III, and the main program in Section IV. The main program calculates the magnetic current coefficient V of [1, eq. (9)] by the methods of solution with and without pseudo-image. The method of solution with pseudo-image is described in [1, Sections III to VII]. The method of solution without pseudo-image is described in [1, Appendix A]. The main program reads input data from the file MAUTZ1.DAT and writes output data on the file MAUTZ2.DAT. In Section IV, the contents of the files MAUTZ1.DAT and MAUTZ2.DAT are listed when the input and output data are for the example of [1, Section VIII].

The computer program for the Fourier series method of solution consists of a main program and the subroutines BES, BESJ1, and BESJY. The subroutine BES is the same as the one mentioned in the previous paragraph. The subroutine BESJ1 is described and listed in Section V, the subroutine BESJY

in Section VI, and the main program in Section VII. The main program obtains an approximation for the magnetic current coefficient V of [1, eq. (B-25)] by truncating the infinite series in [1, eq. (B-25)] at $n = N_2$ where N_2 is entered as input data. The main program reads input data from the file MAUTZ3.DAT and writes output data on the file MAUTZ4.DAT. In Section VII, the contents of the files MAUTZ3.DAT and MAUTZ4.DAT are listed when the input and output data are for the example of [1, Section VIII] and $N_2 = 10,000$.

II. THE SUBROUTINE BES

The subroutine BES(N,X) puts

$$\left. \begin{array}{l} J_n(X) \text{ in } BJ(n+1) \\ Y_n(X) \text{ in } BY(n+1) \end{array} \right\} , \quad n = 0, 1, 2, \dots, N \quad (1)$$

where J_n is the Bessel function of the first kind of order n , and Y_n is the Bessel function of the second kind of order n . Moreover, N is a non-negative integer and X is a non-negative real number. The subroutine BES is listed at the end of this section. In the COMMON statement on line 3 of this listing, Y0, PI2, PI4, and PI7 are input variables and BJ and BY are the output variables that appear in (1). The elements of Y0 will be described later. Their values should not deeply concern the user because he will never have to change them. The values of the input variables

Y0(1), Y0(2), ..., Y0(33) are listed as

```
-0.3072582E+04 0.-7368758E+04-0.6085100E+03 0.1710234E+02-0.2271001E+00
0.1600171E-02-0.5961089E-05 0.9545773E-08 0.4163150E+05 0.3420211E+03
0.1C000C0E+01-0.6024727E+04 0.1613512E+04-0.7532210E+02 0.1402590E+01
-0.12756C2E-01 0.5832787E-04-0.1107698E-06 0.3072946E+05 0.2886431E+03
0.10C000C0E+01 0.9999999E+00-0.1097659E-02 0.2461455E-04 0.1C00000E+01
0.1829893E-02-0.3191328E-04-0.1562498E-01 0.1427079E-03-0.5937434E-05
0.46E7498E-01-0.1998720E-03 0.7317495E-05
```

where the j th number in the i th row is $Y_0(5(i-1)+j)$ for $j=1, 2, \dots, 5$ and $i=1, 2, 3, \dots, 7$. The values of the remaining input variables in the common statement are given by

$$\begin{aligned} PI2 &= 2/\pi \\ PI4 &= \pi/4 \\ PI7 &= 3\pi/4 \end{aligned} \quad (2)$$

Minimum allocations are given by

COMMON BJ(N+1), BY(N+1)

DIMENSION AJ(11+N+2[X])

where $[X]$ is the largest integer that does not exceed X .

The Bessel functions $\{J_n(X), n=0, 1, 2, \dots, N\}$ are calculated in lines 5 to 23. As suggested in [2, Sec. 9.12., Example 1], $J_{MZ}(X)$ and $J_{MZ-1}(X)$ are set equal to the arbitrary values of zero and 10^{-20} , respectively, where

$$MZ = 10 + N + 2[X] \quad (3)$$

This is done in lines 5 to 8 where $J_{MZ}(X)$ and $J_{MZ-1}(X)$ are stored in $AJ(MZ+1)$ and $AJ(MZ)$, respectively. In DO loop 16, the recurrence relation [2, eq. (9.1.27)]

$$J_n(X) = \frac{2(n+1)}{X} J_{n+1}(X) - J_{n+2}(X) \quad (4)$$

is used to calculate $\{J_n(X), n = MZ-2, MZ-3, \dots, 0\}$. Line 13 puts $J_{MK-1}(X)$ of (4) in $AJ(MK)$. According to [2, eq.(9.1.46)], the calculated values of $\{J_n(X)\}$ have to be normalized by dividing by α where

$$\alpha = J_0(X) + 2J_2(X) + 2J_4(X) + \dots \quad (5)$$

Each of the calculated values of $\{J_n(X), n=0, 1, 2, \dots, N\}$ is divided by α in DO loop 17.

The Bessel functions $\cdot Y_n(X)$, $n=0,1,2,\dots,N$ are calculated in lines 24 to 68. For $X \leq 8$, we let [3, eq. (6.8.27)]

$$Y_0(X) = \bar{Y}_0(X) + \frac{2}{\pi} J_0(X) \ln(X) \quad (6)$$

where

$$\bar{Y}_0(X) = \frac{\sum_{m=0}^7 (P0m) X^{2m}}{\sum_{m=0}^2 (Q0m) X^{2m}} \quad (7)$$

where $\{P0m\}$ and $\{Q0m\}$ are the coefficients given under the heading YZERO 6234 on page 309 of [3]. For $X \leq 8$, we also let [3, eq. (6.8.28)]

$$Y_1(X) = \bar{Y}_1(X) + \frac{2}{\pi} [J_1(X) \ln(X) - 1/X] \quad (8)$$

where

$$\frac{\bar{Y}_1(X)}{X} = \frac{\sum_{m=0}^6 (P0m) X^{2m}}{\sum_{m=0}^2 (Q0m) X^{2m}} \quad (9)$$

where $\{P0m\}$ and $\{Q0m\}$ are the coefficients given under the heading YONE 6434 on page 315 of [3]. The coefficients $\{P0m\}$ of (7), $\{Q0m\}$ of (7), $\{P0m\}$ of (9), and $\{Q0m\}$ of (9) reside in Y0(1) to Y0(8), Y0(9) to Y0(11), Y0(12) to Y0(18), and Y0(19) to Y0(21), respectively. Lines 41 and 42 put $\bar{Y}_0(X)$ of (7) in S, and line 44 puts $Y_0(X)$ of (6) in BY(1). Lines 46 and 47 put $\bar{Y}_1(X)/X$ of (9) in S, and line 48 puts $Y_1(X)$ of (8) in BY(2).

For $X > 8$, we let [3, eq. (6.8.17)]

$$Y_n(X) = \sqrt{\frac{2}{\pi X}} [P_n(X) \sin(X_n) + Q_n(X) \cos(X_n)], \quad n=0,1 \quad (10)$$

In (10),

$$x_n = x - \frac{(2n+1)}{4} - \quad (11)$$

and

$$P_0(x) = \sum_{m=0}^2 (P0m)z^{2m} \quad (12)$$

where

$$z = 8/x \quad (13)$$

and $\{P0m\}$ are the coefficients given under the heading PZERO 6501 on page 320 of [3]. Moreover,

$$Q_0(x) = z \sum_{m=0}^2 (P0m)z^{2m} \quad (14)$$

where $\{P0m\}$ are the coefficients given under the heading QZERO 6900 on page 327 of [3]. Regarding (14), there are errors on page 149 of [3]. On that page, each $Q_0(x)/x$ should be replaced by $Q_0(x)/z$ and each $Q_1(x)/x$ by $Q_1(x)/z$. In (10),

$$P_1(x) = \sum_{m=0}^2 (P0m)z^{2m} \quad (15)$$

where $\{P0m\}$ are the coefficients given under the heading PONE 6701 on page 323 of [3], and

$$Q_1(x) = z \sum_{m=0}^2 (P0m)z^{2m} \quad (16)$$

where $\{P0m\}$ are the coefficients given under the heading QONE 7101 on page 331 of [3]. The coefficients $\{P0m\}$ of (12), $\{P0m\}$ of (15), $\{P0m\}$ of (14), and $\{P0m\}$ of (16) reside in Y0(22) to Y0(24), Y0(25) to Y0(27), Y0(28) to Y0(30), and Y0(31) to Y0(33), respectively. Line 54 puts $P_0(x)$ of (12) in S1, line 55 puts $Q_0(x)$ of (14) in S3, line 56 puts x_0 of (11) in S5, and line 57 puts $Y_0(x)$ of (10) in BY(1). Line 59 puts $P_1(x)$ of (15) in S2, line 60 puts $Q_1(x)$ of (16) in S4, line 61 puts x_1 of (11) in S6, and line 62 puts $Y_1(x)$ of (10) in BY(2).

If $N > 1$, then DO loop 21 uses the recurrence relation [2, eq.
(9.1.27)]

$$Y_n(X) = \frac{2(n-1)}{X} Y_{n-1}(X) - Y_{n-2}(X) \quad (17)$$

to put $Y_n(X)$ in BY(n+1) for $n=2,3,\dots,N$.

```

C01 C      LISTING OF THE SUBROUTINE BES
C02          SUBROUTINE BES(N,X)
C03          COMMON Y0(33),PI2,PI4,PI7,BJ(100),BY(100)
C04          DIMENSION AJ(100)
C05          MZ=10+N+2*IFIX(X)
C06          IF(X.LT.1.E-3) MZ=4+N
C07          AJ(MZ+1)=0.
C08          AJ(MZ)=1.E-20
C09          M1=MZ-1
C10          X2=2./X
C11          DO 16 K=1,M1
C12          MK=MZ-K
C13          AJ(MK)=X2*FLCAT(MK)*AJ(MK+1)-AJ(MK+2)
C14 16      CONTINUE
C15          ALP=.5*AJ(1)
C16          DO 15 J=3,MZ,2
C17          ALP=ALP+AJ(J)
C18 15      CONTINUE
C19          ALP=2.*ALP
C20          NF=N+1
C21          DO 17 K=1,NP
C22          EJ(K)=AJ(K)/ALP
C23 17      CONTINUE

```

```

C24      IF(Z-8.) 18,18,19
C25 18   Z1=X*X
C26      Z2=0.
C27      Z3=0.
C28      Z4=0.
C29      Z5=0.
C30      Z6=0.
C31      Z7=0.
C32      IF(Z1.LT.1.E-11) GO TO 22
C33      Z2=Z1*Z1
C34      Z3=Z2*Z1
C35      IF(Z1.LT.1.E-6) GC TO 22
C36      Z4=Z3*Z1
C37      Z5=Z4*Z1
C38      IF(Z1.LT.1.E-4) GC TO 22
C39      Z6=Z5*Z1
C40      Z7=Z6*Z1
C41 22   S=(YC(1)+Y0(2)*Z1+Y0(3)*Z2+Y0(4)*Z3+Y0(5)*Z4+Y0(6)*Z5+
C42      1 Y0(7)*Z6+Y0(8)*Z7)/(Y0(9)+Y0(10)*Z1+Y0(11)*Z2)
C43      TLG=ALCG(X)
C44      EY(1)=S+PI2*BJ(1)*TLG
C45      IF(N.LE.0) RETURN
C46      S=(Y0(12)+Y0(13)*Z1+Y0(14)*Z2+Y0(15)*Z3+Y0(16)*Z4+
C47      1 Y0(17)*Z5+Y0(18)*Z6)/(Y0(19)+Y0(20)*Z1+Y0(21)*Z2)
C48      EY(2)=X*S+PI2*(BJ(2)*TLG-1./X)
C49      GO TO 20
C50 19   Z=8./X
C51      Z1=Z*Z
C52      Z2=Z1*Z1
C53      S=SQRT(PI2/X)
C54      S1=Y0(22)+Y0(23)*Z1+Y0(24)*Z2
C55      S3=Z*(YC(28)+Y0(29)*Z1+Y0(30)*Z2)
C56      S5=X-PI4
C57      PY(1)=S*(S1*SIN(S5)+S3*CCS(S5))
C58      IF(N.LE.0) RETURN
C59      S2=Y0(25)+Y0(26)*Z1+Y0(27)*Z2
C60      S4=Z*(Y0(31)+Y0(32)*Z1+Y0(33)*Z2)
C61      S6=X-PI7
C62      PY(2)=S*(S2*SIN(S6)+S4*CCS(S6))
C63 20   IF(NF.LE.2) RETURN
C64      DO 21 R=3,NP
C65      R2=R-2
C66      PY(R)=X2*FLCAT(R2)*PY(R-1)-PY(R2)
C67 21   CONTINUE
C68      RETURN
C69      END

```

III. THE SUBROUTINES DECOMP AND SOLVE

The subroutines DECOMP(N , IPS, UL) and SOLVE(N , IPS, UL, B, X) solve a system of linear equations in N unknowns. The input to DECOMP consists of N and the N by N matrix of coefficients on the left-hand side of the matrix equation stored by columns in UL. The output from DECOMP is IPS and UL. This output is fed into SOLVE. The rest of the input to SOLVE consists of N and the column of coefficients on the right-hand side of the matrix equation stored in B. SOLVE puts the solution to the matrix equation in X.

Minimum allocations are given by

COMPLEX UL($N*N$)

DIMENSION SCL(N), IPS(N)

in DECOMP and by

COMPLEX UL($N*N$), B(N), X(N)

DIMENSION IPS(N)

in SOLVE.

More detail concerning DECOMP and SOLVE is on pages 46-49 of [4].

```

001C      LISTING OF THE SUBROUTINE DECCMP
002      SUBROUTINE DECOMP(N,IPS,UL)
003      COMPLEX UL(1600),PIVCT,EM
004      DIMENSION SCL(40),IPS(40)
005      DC 5 I=1,N
006      IPS(I)=I
007      RN=0.
008      J1=I
009      DO 2 J=1,N
010      ULM=ABS(REAL(UL(J1)))+ABS(AIMAG(UL(J1)))
011      J1=J1+N
012      IF(RN-ULM) 1,2,2
013 1    RN=ULM
014 2    CONTINUE
015      SCL(I)=1./RN
016 5    CONTINUE
017      NM1=N-1
018      K2=0
019      DO 17 K=1,NM1
020      BIG=0.
021      DO 11 I=K,N
022      IP=IPS(I)
023      IPK=IP+K2
024      SIZE=(ABS(REAL(UL(IPK)))+ABS(AIMAG(UL(IPK))))*SCL(IP)
025      IF(SIZE-BIG) 11,11,10
026 10    BIG=SIZE
027      IPV=I
028 11    CONTINUE
029      IF(IPV-K) 14,15,14
030 14    J=IPS(K)
031      IPS(K)=IPS(IPV)
032      IPS(IPV)=J
033 15    KPP=IPS(K)+K2
034      PIVOT=UL(KPP)
035      KP1=K+1
036      DO 16 I=KP1,N
037      KP=KPP
038      IP=IPS(I)+K2
039      EM=-UL(IP)/PIVOT
040 18    UL(IP)=-EM
041      DC 16 J=KP1,N
042      IP=IP+N
043      KP=KP+N
044      UL(IP)=UL(IP)+EM*UL(KP)
045 16    CONTINUE
046      K2=K2+N
047 17    CONTINUE
048      RETURN
049      END

```

050C LISTING OF THE SUBROUTINE SCLVE
051 SUBROUTINE SCLVE(N,IPS,UL,B,X)
052 COMPLEX UL(1600),B(40),X(40),SUM
053 DIMENSION IPS(40)
054 NP1=N+1
055 IP=IPS(1)
056 X(1)=B(IP)
057 DO 2 I=2,N
058 IP=IPS(I)
059 IPB=IP
060 IM1=I-1
061 SUM=0.
062 DO 1 J=1,IM1
063 SUM=SUM+UL(IF)*X(J)
064 1 IP=IP+N
065 2 X(I)=B(IP)-SUM
066 K2=N*(N-1)
067 IP=IPS(N)+K2
068 X(N)=X(N)/UL(IP)
069 DO 4 IBACK=2,N
070 I=NP1-IEACK
071 K2=K2-N
072 IP1=IPS(I)+K2
073 IP1=I+1
074 SUM=0.
075 IP=IP1
076 DO 3 J=IP1,N
077 IP=IP+N
078 3 SUM=SUM+UL(IP)*X(J)
079 4 X(I)=(X(I)-SUM)/UL(IP)
080 RETURN
081 END

IV. THE MAIN PROGRAM FOR THE METHODS OF SOLUTION WITH AND WITHOUT PSEUDO-IMAGE

The main program for the methods of solution with and without pseudo-image calculates the magnetic current coefficient V of [1, eq. (9)] by means of the methods of solution with and without pseudo-image. The method of solution with pseudo-image is described in [1, Sections III to VII]. The method of solution without pseudo-image is described in [1, Appendix A]. Input data are read from the file MAUTZ1.DAT, output data are written on the file MAUTZ2.DAT, and the subroutines BES, DECOMP, and SOLVE are called. The subroutine BES was described and listed in Section II and the subroutines DECOMP and SOLVE in Section III.

The main program for the methods of solution with and without pseudo-image is listed at the end of this section. In the open statements on lines 9 and 10 of this listing, MAUTZ1.DAT is the input data file and MAUTZ2.DAT is the output data file. The input data are read early in the program according to

```
      READ(20, 11) N, NG, BK, PINC  
      11   FORMAT(2I3, 2E14.7)  
      READ(20, 13)(X(I), I = 1,N)  
      13   FORMAT(5E14.7)  
      READ(20, 13)(Y(I), I = 1,N)  
      READ(20, 13)(YO(I), I = 1, 33)  
      READ(20, 13)(XG(I), I = 1, NG)  
      READ(20, 13)(AG(I), I = 1, NG)
```

Here, N is the integer that appears in [1, eq. (22)]. That is, N is the number of electric current expansion functions on the complete conducting

surface S^{sc} . An NG-point Gaussian quadrature formula is used whenever Gaussian quadrature is called for. Specifically, the integral from -1 to 1 with respect to x of a function $f(x)$ is approximated by [5,

Appendix A]

$$\int_{-1}^1 f(x)dx = \sum_{i=1}^{NG} A_i^{(NG)} f(X_i^{(NG)}) \quad (18)$$

where $X_i^{(NG)}$ and $A_i^{(NG)}$ are, respectively, the abscissa and weight given in [5, Appendix A]. Still in the first read statement, BK is the wave number k that appears in [1, eq. (44)], and PINC is the incident angle ψ^{inc} in [1, eq. (44)]. In the next two read statements, $(X(I), Y(I))$ are the (x,y) coordinates of the point P_I in [1, Fig. 1]. That is, $X(I)$ and $Y(I)$ are, respectively, the quantities x_I and y_I in [1, eq. (53)]. Here, BK is in reciprocal meters, PINC is in radians, and $(X(I), Y(I))$ are in meters. The array YO contains input data for the subroutine BES. The values of the elements of YO were given in Section II. These values should not deeply concern the user because he will never have to change them. In the last two read statements, XG(I) and AG(I) are, respectively, the abscissa $X_I^{(NG)}$ and weight $A_I^{(NG)}$ in (18).

Minimum allocations are given by

```
COMMON BJ(2), BY(2)
COMPLEX Z(N*N), VA(N), VINC(N), CURI(N), CURA(N)
DIMENSION X(N), Y(N), XG(NG), AG(NG), DX(N)
DIMENSION DY(N), G(N), XP(N), YP(N), IPS(N)
```

In the present program, BJ(2) and BY(2) are sufficient. However, BJ(100) and BY(100) were used in the listing of this program. The reason for this is explained in the next two sentences. The allocations for BJ and BY in

the present program must be the same as the allocations in the subroutine BES. The same subroutine BES was also used with the program of Section VII, and during that usage BJ(2) and BY(2) did not suffice.

Immediately after the main program at the end of this section, the contents of the input data file MAUTZ1.DAT and the output data file MAUTZ2.DAT are listed when the input and output data are for the example of [1, Section VIII]. The output data file MAUTZ2.DAT contains all the data put out by the write statements in the main program for the methods of solution with and without pseudo-image. The contents of the output data file MAUTZ2.DAT are described in the next two paragraphs.

The input data are written out immediately after they are read in. The four numbers in the i th line under the heading "VINC" are, from left to right, $\text{Re}(4kV_{2i-1}^{\text{inc}})$, $\text{Im}(4kV_{2i-1}^{\text{inc}})$, $\text{Re}(4kV_{2i}^{\text{inc}})$, and $\text{Im}(4kV_{2i}^{\text{inc}})$ where V_{2i-1}^{inc} and V_{2i}^{inc} are the $(2i-1)$ th and $(2i)$ th elements of the column vector \vec{V}^{inc} that appears in [1, eq. (23)]. Moreover, "Re" denotes real part, "Im" denotes imaginary part, and k is the wave number that appears in [1, eq. (44)]. Similarly, the numbers written under the heading "VA" are the elements of $4k\vec{V}^a$, those written under the heading "Z" are the elements of $\frac{4k}{r} Z_{,1}$, those written under the heading "CURI" are the elements of \vec{I}^{inc} , and those written under the heading "CURA" are the elements of \vec{I}^a . Here, \vec{V}^a appears in [1, eq. (34)], $Z_{,1}$ denotes the first column of the square matrix Z that appears in [1, eq. (23)], r is the intrinsic impedance that appears in [1, eq. (45)], \vec{I}^{inc} appears in [1, eq. (23)], and \vec{I}^a appears in [1, eq. (34)].

Other output variables are called CA, CP, CINC, YHS, YAB, TI, V, YABW, and VW. They are conspicuously identified in the output data file MAUTZ2.DAT. For instance, the real and imaginary parts of CA are preceded

by "CA=". The output variable CINC, being real, is a single number preceded by "CINC=". Each output variable mentioned in the first sentence of this paragraph corresponds to a quantity in [1]. This correspondence is revealed in Table 1.

Table 1. Computer program output variables and their corresponding quantities in [1] or in the text.

| Output variable | Corresponding quantity in [1] or in the text | Equation(s) where the quantity appears |
|-----------------|--|--|
| N | N | [1, eq. (22)] |
| NG | NG | (18) |
| BK | k | [1, eq. (44)] |
| PINC | \dot{p}^{inc} | [1, eq. (44)] |
| X(I) | x_I | [1, eq. (53)] |
| Y(I) | y_I | [1, eq. (53)] |
| YO | POm and QOm | (7), (9), (12), (15), (14), (16) |
| XG(I) | $x_I^{(NG)}$ | (18) |
| AG(I) | $A_I^{(NG)}$ | (18) |
| VINC(I) | $4kV_I^{inc}$ | [1, eq. (23)] |
| VA(I) | $4kV_I^a$ | [1, eq. (34)] |
| Z(I) | $\frac{4k}{\cdot} Z_{I1}$ | [1, eq. (23)] |
| CA | C_A | [1, eq. (86)] |
| CP | C_p | [1, eq. (86)] |
| CINC | krC^{inc} | [1, eq. (116)] |
| CURI(I) | γI_I^{inc} | [1, eq. (23)] |
| CURA(I) | γI_I^a | [1, eq. (34)] |
| YHS | $2k\gamma Y^{hs}$ | [1, eq. (76)] |
| YAB | $4kn(Y^a + Y^b)$ | [1, eq. (10)] |
| TI | $4knI$ | [1, eq. (10)] |
| V | V | [1, eq. (10)] |
| YABW | $4kn(Y^{aw} + Y^{bw})$ | [1, eq. (A-25)] |
| VW | V^w | [1, eq. (A-26)] |

Lines 32 and 33 put $\cos \phi^{inc}$ and $\sin \phi^{inc}$ of [1, eq. (44)] in CSP and SNP, respectively. Lines 35 to 37 define the common variables (2) that are input data for the subroutine BES. With regard to [1, eqs. (57) and (58)], DO loop 37 puts $0.5k(x_{J+1} - x_J)$ in $DX(J)$ and $0.5k(y_{J+1} - y_J)$ in $DY(J)$. DO loop 37 also puts $0.5\gamma_J$ in $G(J)$, kx_J^+ in $XP(J)$, and ky_J^+ in $YP(J)$ where γ_J , x_J^+ , and y_J^+ are given by [1, eqs. (53), (55), and (56)].

In nested DO loops 38 and 39, $\frac{4k}{n} Z_{IJ}$ is put in $Z((J-1)*N+I)$ where Z_{IJ} is given by [1, eq. (52)]. Thus, as the indices I and J traverse their ranges, the upper triangular portion of the square matrix $\frac{4k}{n} Z$ of [1, eq. (23)] is stored by columns in the singly dimensioned array Z.

When $J=N$, DO loop 39 puts $4kV_I^{inc}$ in $VINC(I)$ and $4kV_I^a$ in $VA(I)$ where V_I^{inc} and V_I^a are given by [1, eqs. (67) and (74)].

The calculation of the off-diagonal elements of $\frac{4k}{n} Z$ of [1, eq. (23)] is described in this paragraph and the next two paragraphs. Replacing ij by IJ in [1, eq. (52)], multiplying both sides of that equation by $4k/n$, changing the variables of integration therein to make the ranges of integration from -1 to 1, and then approximating both integrals by means of (18), we obtain

$$\frac{4k}{n} Z_{IJ} = \frac{\gamma_I \gamma_J}{4} \sum_{K=1}^{NG} A_K^{(NG)} \sum_{L=1}^{NG} A_L^{(NG)} H_o^{(2)}(\alpha_{IJKL}) \quad (19)$$

where

$$\alpha_{IJKL} = \sqrt{(XX)^2 + (YY)^2} \quad (20)$$

where

$$XX = kx_I^+ - kx_J^+ + \frac{k}{2} (x_{I+1} - x_I) X_K^{(NG)} - \frac{k}{2} (x_{J+1} - x_J) X_L^{(NG)} \quad (21)$$

and

$$YY = ky_I^+ - ky_J^+ + \frac{k}{2} (y_{I+1} - y_I) X_K^{(NG)} - \frac{k}{2} (y_{J+1} - y_J) X_L^{(NG)} \quad (22)$$

Expressions (21) and (22) were obtained by using [1, eqs. (57) and (58)] to express the trigonometric functions in [1, eq. (54)].

Nested DO loops 40 and 41 perform the double summation in (19). The DO loop indices K and L obtain, respectively, the summation indices K and L in (19). DO loop 41 accumulates in Z2 the summation with respect to L in (19). DO loop 40 accumulates in Z1 the summation with respect to K in (19). Line 80 puts α_{ijkl} of (20) in X1. Depending on whether J = N, either line 82 or line 84 puts the Bessel functions $J_o(\cdot_{ijkl})$ and $Y_o(\cdot_{ijkl})$ in BJ(1) and BY(1), respectively. According to [2, eq. (9.1.4)],

$$H_n^{(2)}(x) = J_n(x) - jY_n(x) \quad (23)$$

Line 86 uses (23) with n=0 and $x=\alpha_{ijkl}$ to properly increment Z2. Line 93 puts the right-hand side of (19) in $Z((J-1)*N+I)$.

If, in (19), I and J are interchanged, and the order of summation is interchanged, the right-hand side of (19) remains unchanged. Therefore, Z_{IJ} of (19) is symmetric, that is,

$$Z_{JI} = Z_{IJ} \quad (24)$$

Using (24), line 102 puts $\frac{4k}{n} Z_{JI}$ of (19) in $Z((I-1)*N+J)$. Thus, as I and J traverse their ranges, line 102 stores by columns the lower triangular portion of the square matrix $\frac{4k}{n} Z$ of [1, eq. (23)] in the singly dimensioned array Z.

Multiplying both sides of [1, eq. (67)] by 4k, replacing i by I therein, expanding $\cos(\cdot_I - \cdot^{inc})$, and using [1, eqs. (57) and (58)] to express the resulting $\cos \cdot_I$ and $\sin \cdot_I$ terms, we obtain

$$4kV_I^{inc} = 4e_I^{jk(x_I^+ \cos \phi^{inc} + y_I^+ \sin \phi^{inc})} \left(\frac{\sin(S1)}{S1} \right) \quad (25)$$

where

$$S1 = 0.5k(x_{I+1} - x_I) \cos \phi^{inc} + 0.5k(y_{I+1} - y_I) \sin \phi^{inc} \quad (26)$$

Equation (25) is written with the understanding that $\sin(S1)/S1$ should be replaced by 1 whenever $S1 = 0$. If $J = N$, then line 96 inside nested DO loops 38 and 39 puts the right-hand side of (26) in $S1$. Line 100 puts the right-hand side of (25) in $VINC(I)$.

Since the coordinates (x_N, y_N) and (x_{N+1}, y_{N+1}) in [1] are given by

$$\left. \begin{array}{l} (x_N, y_N) = (0, -w) \\ (x_{N+1}, y_{N+1}) = (0, w) \end{array} \right\} \quad (27)$$

it is evident from [1, eqs. (55) and (56)] that

$$\left. \begin{array}{l} kx_N^+ = 0 \\ ky_N^+ = 0 \end{array} \right\} \quad (28)$$

It is also evident from [1, eq. (53)] that

$$\left. \begin{array}{l} k(x_{N+1} - x_N) = 0 \\ k(y_{N+1} - y_N) = y_N \end{array} \right\} \quad (29)$$

Taking advantage of (28) and (29), lines 107 to 110 put $4kV_N^{inc}$ of (25) in $VINC(N)$.

It is evident from (27) and (29) that

$$kw = 0.5y_N \quad (30)$$

Multiplying both sides of [1, eq. (74)] by $4k$, replacing i by I therein, changing the variables of integration to make the ranges of integration from -1 to 1 , approximating the integrals by means of (18), then substituting (30) for kw and [1, eqs. (57) and (58)] for the cosines and sines, we obtain

$$4kV_I^a = -2j \frac{\gamma_I \gamma_N}{4} \sum_{K=1}^{NG} A_K^{(NG)} (XX) \sum_{L=1}^{NG} \frac{A_L^{(NG)} \sqrt{1 - (x_L^{(NG)})^2} H_1^{(2)}(\alpha_{INKL})}{\alpha_{INKL}} \quad (31)$$

where

$$\alpha_{INKL} = \sqrt{(XX)^2 + (YY)^2} \quad (32)$$

In (32), XX is the right-hand side of (21) with J replaced by N and YY is the right-hand side of (22) with J replaced by N . According to (28) and (29), the XX that appears explicitly in (31) is the same as the one in (32). When $J=N$, DO loop 39 puts the right-hand side of (31) in $VA(I)$. When $J=N$, nested DO loops 40 and 41 perform the double summation in (31). The DO loop indices K and L obtain, respectively, the summation indices K and L in (31). DO loop 41 accumulates in $V2$ the summation with respect to L in (31). DO loop 40 accumulates in $V1$ the summation with respect to K in (31). Line 80 puts α_{INKL} of (32) in $X1$. Line 84 puts the Bessel functions $J_1(\alpha_{INKL})$ and $Y_1(\alpha_{INKL})$ in $BJ(2)$ and $BY(2)$, respectively. Line 85 uses (23) with $n=1$ and $x = \alpha_{INKL}$ to properly increment $V2$. Line 95 puts the right-hand side of (31) in $VA(I)$. Line 105 obtains [1, eq. (68)] by setting $VA(N) = 0$.

In DO loop 21, $\frac{4k}{n} Z_{II}$ is put in $Z((I-1)*N+I)$ where Z_{II} is given by [1, eq. (64)]. Thus, as the index I traverses its range, the diagonal elements of the square matrix $\frac{4k}{n} Z$ of [1, eq. (23)] are stored in the singly dimensioned array Z . Storage of $\frac{4k}{n} Z$ of [1, eq. (23)] is by columns in the singly dimensioned array Z . When $I=N$, C_A and C_I of [1, eq. (86)] are put

in CA and CP, respectively, and $k^r C^{inc}$ of [1, eq. (116)] is put in CINC.

The calculation of the diagonal elements of $\frac{4k}{\pi} Z$ of [1, eq. (23)] is described as follows. Replacing i by I in [1, eq. (64)], multiplying both sides of that equation by $4k/\pi$, changing the variables of integration therein to make the ranges of integration from -1 to 1, and then approximating both integrals by means of (18), we obtain

$$\frac{4k}{\pi} Z_{II} = \frac{\gamma_I^2}{4} \left[\left[4 + \frac{j4}{\pi} (3 - 2 \ln (0.5 \gamma_I)) \right] + \sum_{K=1}^{NG} A_K^{(NG)} \sum_{L=1}^{NG} U_L \right] \quad (33)$$

where

$$U_L = A_L^{(NG)} [H_0^{(2)}(XX) - 1 + \frac{j2}{\pi} \ln (0.5 \gamma XX)] \quad (34)$$

where

$$XX = 0.5 \gamma_I \left| X_K^{(NG)} - X_L^{(NG)} \right| \quad (35)$$

Prior to DO loop 21, line 115 puts γ in GAM. This γ is the e^γ that appears in [2, p. 2]. Line 122 puts in Z1 the square bracketed quantity in (33). Nested DO loops 22 and 23 perform the double summation in (33). The DO loop indices K and L obtain, respectively, the summation indices K and L in (33). DO loop 23 accumulates in Z2 the summation with respect to L in (33). Since the square bracketed quantity in [1, eq. (60)] approaches zero as x approaches zero, the term for which L=K in (33) is zero and therefore does not contribute to Z2. Line 136 puts XX of (35) in XX. Line 137 puts the Bessel functions $J_0(XX)$ and $Y_0(XX)$ in BJ(1) and BY(1), respectively. Line 138 uses (23) with n=0 and x=XX to put U1 of (34) in U1. Line 139 accumulates in Z2 the summation with respect to L in (33). Do loop 22 accumulates in Z1 the quantity in the braces in (33). Line 153 puts the right-hand side of (33) in Z((I-1)*N+I).

The calculation of C_A and C_{γ} of [1, eq. (86)] is described in this paragraph and the next paragraph. Substituting (30) into [1, eq. (89)] and using (18) to approximate both integrals in [1, eq. (89)], we obtain

$$C_A = I_A + \sum_{K=1}^{NG} A_K^{(NG)} \sqrt{1 - (X_K^{(NG)})^2} \sum_{L=1}^{NG} \sqrt{1 - (X_L^{(NG)})^2} U_1 \quad (36)$$

where U_1 is given by (34) in which XX is given by (35) with γ_I replaced by γ_N . Substitution of (30) into [1, eq. (96)] gives

$$I_A = \frac{\pi}{2} [\frac{\pi}{2} + j(\frac{1}{4} - \ln(\frac{\gamma_N}{8}))] \quad (37)$$

Substituting (30) and [1, eq. (99)] into [1, eq. (90)] and using (18) to approximate both integrals in [1, eq. (90)], we obtain

$$C_{\gamma} = j\pi + \sum_{K=1}^{NG} \frac{A_K^{(NG)} X_K^{(NG)}}{\sqrt{1 - (X_K^{(NG)})^2}} \sum_{L=1}^{NG} \frac{X_L^{(NG)} U_1}{\sqrt{1 - (X_L^{(NG)})^2}} \quad (38)$$

where U_1 is the same as in (36).

When $I=N$ inside DO loop 21, C_A of (36) and C_{γ} of (38) are put in CA and CP, respectively. Line 124 puts I_A of (37) in CA. Line 125 puts $j\pi$ of (38) in CP. DO loop 23 accumulates in CA1 the sum with respect to L in (36). DO loop 23 also accumulates in CP1 the sum with respect to L in (38). Line 138 puts U_1 of (36) in U1. Inside DO loop 22, lines 149 and 150 accumulate C_A of (36) and C_{γ} of (38) in CA and CP, respectively.

Multiplying [1, eq. (118)] by k' , using (18) to approximate the integral therein, and substituting (30) for kw , we obtain

$$k' C^{inc} = 0.5 \gamma_N \cos \phi^{inc} \sum_{K=1}^{NG} A_K^{(NG)} \sqrt{1 - (X_K^{(NG)})^2} \cos(0.5 \gamma_N X_K^{(NG)} \sin \phi^{inc}) \quad (39)$$

When $I=N$ inside DO loop 21, DO loop 22 accumulates in CINC the summation with respect to K in (39). Outside nested DO loops 21 and 22, line 156 performs the required multiplication by $0.5 \cdot N \cos \hat{\theta}^{inc}$ so that $k \cdot C^{inc}$ of (39) will finally be stored in CINC.

Line 162 puts in CURI(I) the Ith element of $\hat{r}\hat{I}^{inc}$ where \hat{I}^{inc} is the column vector that satisfies [1, eq. (23)]. Line 163 puts in CURA(I) the Ith element of $\hat{r}\hat{I}^a$ where \hat{I}^a is the column vector that satisfies [1, eq. (34)]. In the previous two sentences, $I=1,2,\dots,N$. Line 168 puts $2krY^{hs}$ of [1, eq. (86)] in YHS. Line 169 puts $8krY^{hs}$ in YAB. DO loop 26 adds to YAB the product of $4kr$ with the summation with respect to j in [1, eq. 115]. Thus, after exit from DO loop 26, $4kr(Y^a + Y^b)$ of [1, eq. (115)] will reside in YAB. Line 173 sets VA(N) equal to $\hat{r}Y_N$ which, according to (30), is 2^{-kw} so that $-8kC_J^-$ will reside in VA(J) for $J=1,2,\dots,N$. Here C_J^- is given by [1, eqs. (109) and (102)]. DO loop 27 accumulates in TI the product of $-8kr$ with the summation with respect to j in [1, eq. (116)]. Line 178 puts $4krI$ of [1, eq. (116)] in TI. Line 179 puts V of [1, eq. (10)] in V.

Lines 183 to 188 perform the additional calculations that are necessary to determine V^W of [1, eq. (A-26)]. DO loop 35 sets VA(J) = 0 for $J=1,2,\dots,N-1$, so that, after exit from DO loop 35, $4k(V_J^{aw} - V_J^{bw})$ of [1, eq. (A-23)] will reside in VA(J) for $J=1,2,\dots,N$. Line 186 puts $\hat{r}(I_N^{aw} - I_N^{bw})$ of [1, eq. (A-24)] in CURA(N). Line 187 puts $4kr(Y^{aw} + Y^{bw})$ of [1, eq. (A-25)] in YABW. Finally, line 188 puts V^W of [1, eq. (A-26)] in VW.

Our description of the main program for the methods of solution with and without pseudo-image is summarized in Table 2 where key variables in this program are listed. Each variable is identified by the line where it was read in, defined or incremented, and by its corresponding quantity in [1] or in the text.

Table 2. Key variables in the computer program, program lines where they are read in, defined or incremented, and their corresponding quantities in [1] or in the text.

| Program variable | Program line | Corresponding quantity in [1] or in the text | Equation(s) where the quantity appears |
|------------------|--------------|--|--|
| N | 11 | N | [1, eq. (22)] |
| NG | 11 | NG | (18) |
| BK | 11 | k | [1, eq. (44)] |
| PINC | 11 | ϕ^{inc} | [1, eq. (44)] |
| X(I) | 15 | x_I | [1, eq. (53)] |
| Y(I) | 19 | y_I | [1, eq. (53)] |
| YO | 22 | P_{0m} and Q_{0m} | (7), (9), (12), (15), (14), (16) |
| XG(I) | 25 | $x_I^{(NG)}$ | (18) |
| AG(I) | 28 | $A_I^{(NG)}$ | (18) |
| CSP | 32 | $\cos \phi^{inc}$ | [1, eq. (44)] |
| SNP | 33 | $\sin \phi^{inc}$ | [1, eq. (44)] |
| DX(J) | 44 | $0.5k(x_{J+1} - x_J)$ | (21) |
| DY(J) | 45 | $0.5k(y_{J+1} - y_J)$ | (22) |
| G(J) | 46 | $0.5\gamma_J$ | [1, eq. (53)] |
| XP(J) | 47 | kx_J^+ | [1, eq. (55)] |
| YP(J) | 48 | ky_J^+ | [1, eq. (56)] |
| X1 | 80 | α_{IJKL} | (20) |
| BJ(1) | 82 | $J_o(\alpha_{IJKL})$ | (19), (23) |
| BY(1) | 82 | $Y_o(\alpha_{IJKL})$ | (19), (23) |
| Z2 | 86 | The sum on L | (19) |
| Z1 | 88 | The double sum | (19) |
| Z((J-1)*N+I) | 93 | $\frac{4k}{n} Z_{IJ}$ | (19) |
| Z((I-1)*N+J) | 102 | $\frac{4k}{n} Z_{JI}$ | (24), (19) |
| S1 | 96 | S1 | (26) |
| VINC(I) | 100 | $4kV_I^{inc}$ | (25) |
| VINC(N) | 110 | $4kV_N^{inc}$ | (25) |
| X1 | 80 | α_{INKL} | (32) |
| BJ(2) | 84 | $J_1(\alpha_{INKL})$ | (31), (23) |
| BY(2) | 84 | $Y_1(\alpha_{INKL})$ | (31), (23) |

Table 2. (continued)

| Program variable | Program line | Corresponding quantity in [1] or in the text | Equation(s) where the quantity appears |
|------------------|--------------|--|--|
| V2 | 85 | The sum on L | (31) |
| V1 | 89 | The double sum | (31) |
| VA(I) | 95 | $4kV_I^a$ | (31) |
| VA(N) | 105 | $4kV_N^a$ | [1, eq. (68)] |
| GAM | 115 | ? | (33) |
| Z1 | 122 | The square bracketed quantity | (33) |
| XX | 136 | XX | (35) |
| BJ(1) | 137 | $J_o(XX)$ | (34), (23) |
| BY(1) | 137 | $Y_o(XX)$ | (34), (23) |
| U1 | 138 | U1 | (34) |
| Z2 | 139 | The sum on L | (33) |
| Z1 | 146 | The quantity in the {} braces | (33) |
| $Z((I-1)*N+I)$ | 153 | $\frac{4k}{\eta} Z_{II}$ | (33) |
| CA | 124 | I_A | (37) |
| CP | 125 | j^π | (38) |
| CA1 | 142 | The sum on L | (36) |
| CP1 | 143 | The sum on L | (38) |
| CA | 149 | C_A | (36) |
| CP | 150 | C_s | (38) |
| CINC | 151 | The sum on K | (39) |
| CINC | 156 | $k\eta C^{inc}$ | (39) |
| CURI(I) | 162 | ηI_I^{inc} | [1, eq. (23)] |
| CURA(I) | 163 | ηI_I^a | [1, eq. (34)] |

Table 2. (continued)

| Program variable | Program line | Corresponding quantity in [1] or in the text | Equation(s) where the quantity appears |
|------------------|--------------|--|--|
| YHS | 168 | $2knY^{hs}$ | [1, eq. (86)] |
| YAB | 169 | $8krY^{hs}$ | [1, eq. (115)] |
| YAB | 171 | $4kn(Y^a + Y^b)$ | [1, eq. (115)] |
| VA(J) | 95,173 | $-8kC_J^-$ | [1, eqs. (109) and (102)] |
| TI | 176 | $-8kr$ multiplied by the sum on j | [1, eq. (116)] |
| TI | 178 | $4krI$ | [1, eq. (116)] |
| V | 179 | V | [1, eq. (10)] |
| VA(J) | 173,184 | $4k(V_J^{aw} - V_J^{bw})$ | [1, eq. (A-23)] |
| CURA(N) | 186 | $n(I_N^{aw} - I_N^{bw})$ | [1, eq. (A-20)] |
| YABW | 187 | $4kn(Y^{aw} + Y^{bw})$ | [1, eq. (A-25)] |
| VW | 188 | V^w | [1, eq. (A-26)] |

```

C01C      LISTING OF THE MAIN PROGRAM FOR THE METHODS OF
C02C      SOLUTION WITH AND WITHOUT PSEUDOC-IMAGE
C03      COMPLEX U2,Z1,V1,Z2,V2,Z(1600),VA(40),VINC(40),CA
C04      COMPLEX CP,CA1,CP1,U1,CURI(40),CURA(40),YHS,YAB,TI
C05      COMPLEX V,YABW,VW
C06      COMMON Y0(33),PI2,PI4,PI7,BJ(100),BY(100)
C07      DIMENSION X(40),Y(40),XG(10),AG(10),EX(40)
C08      DIMENSION DY(40),G(40),XP(40),YP(40),IPS(40)
C09      OPEN(UNIT=20,FILE='MAUTZ1.DAT')
C10      OPEN(UNIT=21,FILE='MAUTZ2.DAT')
C11      READ(20,11) N,NG,BK,PINC
C12 11    FORMAT(2I3,2E14.7)
C13      WRITE(21,12) N,NG,BK,PINC
C14 12    FORMAT(' N NG',6X,'BK',11X,'PINC'/1X,2I3,2E14.7)
C15      READ(20,13)(X(I),I=1,N)
C16 13    FORMAT(5E14.7)
C17      WRITE(21,14)(X(I),I=1,N)
C18 14    FORMAT(' X'/(1X,5E14.7))
C19      READ(20,13)(Y(I),I=1,N)
C20      WRITE(21,15)(Y(I),I=1,N)
C21 15    FORMAT(' Y'/(1X,5E14.7))
C22      READ(20,13)(Y0(I),I=1,33)
C23      WRITE(21,16)(Y0(I),I=1,33)
C24 16    FORMAT(' Y0'/(1X,5E14.7))
C25      READ(20,13)(XG(I),I=1,NG)
C26      WRITE(21,17)(XG(I),I=1,NG)
C27 17    FORMAT(' XG'/(1X,5E14.7))
C28      READ(20,13)(AG(I),I=1,NG)
C29      WRITE(21,18)(AG(I),I=1,NG)
C30 18    FORMAT(' AG'/(1X,5E14.7))
C31      BK5=.5*BK
C32      CSP=CCS(PINC)
C33      SNP=SIN(PINC)
C34      PI=3.141593
C35      PI2=2./PI
C36      PI4=PI/4.
C37      PI7=.75*PI
C38      U2=(0.,-2.)
C39      DO 37 J=1,N
C40      J1=J+1
C41      IF(J.EQ.N) J1=1
C42      D1=BK5*(X(J1)-X(J))
C43      D2=BK5*(Y(J1)-Y(J))
C44      DX(J)=D1
C45      DY(J)=D2
C46      G(J)=SQRT(D1*D1+D2*D2)
C47      XP(J)=BK5*(X(J1)+X(J))
C48      YP(J)=BK5*(Y(J1)+Y(J))
C49 37    CONTINUE
C50      NM=N-1
C51      DO 38 J=2,N
C52      II=(J-1)*N
C53      CXJ=DX(J)

```

```

C54      D YJ=DY (J)
055      GJ=G (J)
056      XPJ=XP (J)
057      YPJ=YP (J)
058      JM=J-1
059      DO 39 I=1,JM
C60      DXI=DX (I)
061      DYI=DY (I)
062      GI=G (I)
063      XPI=XP (I)
C64      YPI=YP (I)
065      XIJ=XPI-XPJ
C66      YIJ=YPI-YPJ
067      Z1=(0.,0.)
068      IF(J.EQ.N) V1=(0.,0.)
069      DO 40 K=1,NG
070      AK=AG (K)
071      XK=XIJ+XG (K)*DXI
072      YK=YIJ+XG (K)*DYI
073      Z2=(0.,0.)
074      IF(J.EQ.N) V2=(0.,0.)
075      DO 41 L=1,NG
C76      XL=XG (L)
077      AL=AG (L)
078      XX=XK-XL*DXJ
079      YY=YK-XL*DYJ
080      X1=SQRT(XX*XX+YY*YY)
081      IF(J.EQ.N) GO TO 19
082      CALL EES (0,X1)
083      GO TO 20
C8419    CALL EES (1,X1)
085      V2=AL*SQRT(1.-XL*XL)/X1*CMPLX(BJ(2),-BY(2))+V2
08620    Z2=AL*CMPLX(BJ(1),-BY(1))+Z2
CONTINUE
C88      Z1=AK*Z2+Z1
089      IF(J.EQ.N) V1=AK*XX*V2+V1
09040    CONTINUE
091      GG=GI*GJ
C92      II=II+1
093      Z(II)=GG*Z1
C94      IF(J.NE.N) GO TO 42
095      VA(I)=GG*U2*V1
096      S1=DXI*CSP+DYI*SNP
097      S3=1.
C98      IF(S1.NE.0.) S3=SIN(S1)/S1
099      S2=XPI*CSP+YPI*SNP
100      VINC(I)=8.*GI*S3*CMPLX(CCS(S2),SIN(S2))
10142    JJ=(I-1)*N+J
102      Z(JJ)=Z(II)
10339    CONTINUE
10438    CONTINUE
105      VA(N)=0.
106      GN=G (N)

```

```

107      S1=GN*SNP
108      S3=1.
109      IF(S1.NE.0.) S3=SIN(S1)/S1
110      VINC(N)=8.*GN*S3
111      WRITE(21,30) (VINC(I),I=1,N)
112 29    FORMAT(' VA'/(1X,4E14.7))
113      WRITE(21,29) (VA(I),I=1,N)
114 30    FORMAT(' VINC'/(1X,4E14.7))
115      GAM=1.781072
116      GAM2=.5*GAM
117      IZ=1
118      NP=N+1
119      DO 21 I=1,N
120      GI=G(I)
121      GAMG=GAM*GI
122      Z1=CMPLX(4.,4./PI*(3.-2.*ALCG(GAMG)))
123      IF(I.NE.N) GO TO 24
124      CA=.5*PI*CMPLX(.5*PI,.25- ALOG(.25*GAMG))
125      CP=CMPLX(0.,PI)
126      CINC=0.
127 24    DO 22 K=1,NG
128      Z2=(0.,0.)
129      IF(I.NE.N) GO TO 25
130      CA1=(0.,0.)
131      CP1=(0.,0.)
132 25    XGK=XG(K)
133      DC 23 L=1,NG
134      IF(L.EQ.K) GO TO 23
135      XGL=XG(L)
136      XX=GI*ABS(XGK-XGL)
137      CALL EES(0,XX)
138      U1=AG(L)*CMPLX(BJ(1)-1.,-BY(1)+PI2*ALOG(GAM2*XX))
139      Z2=U1+Z2
140      IF(I.NE.N) GO TO 23
141      SQ=SQRT(1.-XGL*XGL)
142      CA1=SQ*U1+CA1
143      CP1=XGL/SQ*U1+CP1
144 23    CONTINUE
145      AGK=AG(K)
146      Z1=AGK*Z2+Z1
147      IF(I.NE.N) GO TO 22
148      SQ=SQRT(1.-XGK*XGK)
149      CA=AGK*SQ*CA1+CA
150      CP=AGK*XGK/SQ*CP1+CP
151      CINC=CINC+AGK*SQ*COS(S1*XGK)
152 22    CONTINUE
153      Z(IZ)=GI*GI*Z1
154      IZ=IZ+NP
155 21    CONTINUE
156      CINC=GN*CSP*CINC
157      WRITE(21,28) (Z(I),I=1,N)
158 28    FORMAT(' Z'/(1X,4E14.7))
159      WRITE(21,34) CA,CP,CINC

```

```
160 34      FORMAT(' CA=',2E14.7,', CP=',2E14.7/' CINC=',E14.7)
161      CALL DECOMP(N,IPS,Z)
162      CALL SCLVE(N,IPS,Z,VINC,CURI)
163      CALL SCLVE(N,IPS,Z,VA,CURA)
164      WRITE(21,31)(CURI(I),I=1,N)
165 31      FORMAT(' CURI'/(1X,4E14.7))
166      WRITE(21,32)(CURA(I),I=1,N)
167 32      FORMAT(' CURA'/(1X,4E14.7))
168      YHS=GN*GN*CA-CP
169      YAB=4.*YHS
170      DO 26 J=1,NM
171      YAB=YAB+CURA(J)*VA(J)
172 26      CONTINUE
173      VA(N)=2.*PI*GN
174      TI=(0.,0.)
175      DO 27 J=1,N
176      TI=TI+CURI(J)*VA(J)
177 27      CONTINUE
178      TI=4.*CINC-.5*TI
179      V=TI/YAB
180      WRITE(21,33) YHS,YAB,VI,V
181 33      FORMAT(' YHS=',2E14.7,', YAB=',2E14.7/
182      1 ' TI=',2E14.7,', V=',2E14.7)
183      DO 35 J=1,NM
184      VA(J)=0.
185 35      CONTINUE
186      CALL SCLVE(N,IPS,Z,VA,CURA)
187      YABW=.5*YAB+PI*GN*CURA(N)
188      VW=TI/YABW
189      WRITE(21,36) YABW,VW
190 36      FORMAT(' YABW=',2E14.7,', VW=',2E14.7)
191      STOP
192      END
```

C LISTING OF THE INPUT DATA FILE MAUTZ1.DAT

C
36 10 0.1570796E+01 0.3141593E+01
0.000000E+00 0.3026887E-01 0.8988691E-01 0.1770427E+00 0.2890879E+00
0.4226183E+00 0.5735764E+00 0.7373757E+00 0.9090390E+00 0.1083350E+01
0.1255014E+01 0.1418813E+01 0.1569771E+01 0.1703301E+01 0.1815347E+01
0.1902502E+01 0.1962121E+01 0.1992389E+01 0.1992389E+01 0.1962121E+01
0.1902502E+01 0.1815347E+01 0.1703301E+01 0.1569771E+01 0.1418813E+01
0.1255014E+01 0.1083350E+01 0.9090390E+00 0.7373757E+00 0.5735764E+00
0.4226183E+00 0.2890879E+00 0.1770427E+00 0.8988691E-01 0.3026887E-01
0.000000E+00
0.8715574E-01 0.2588190E+00 0.4226183E+00 0.5735764E+00 0.7071068E+00
0.8191520E+00 0.9063078E+00 0.9659258E+00 0.9961947E+00 0.9961947E+00
0.9659258E+00 0.9063078E+00 0.8191520E+00 0.7071068E+00 0.5735764E+00
0.4226183E+00 0.2588190E+00 0.8715574E-01-0.8715574E-01-0.2588190E+00
-0.4226183E+00-0.5735764E+00-0.7071068E+00-0.8191520E+00-0.9063078E+00
-0.9659258E+00-0.9961947E+00-0.9961947E+00-0.9659258E+00-0.9063078E+00
-0.8191520E+00-0.7071068E+00-0.5735764E+00-0.4226183E+00-0.2588190E+00
-0.8715574E-01
-0.3072582E+04 0.7368758E+04-0.6085100E+03 0.1710234E+02-0.2271001E+00
0.1600171E-02-0.5961089E-05 0.9545773E-08 0.4163150E+05 0.3420211E+03
0.1000000E+01-0.6024727E+04 0.1613512E+04-0.7532210E+02 0.1402590E+01
-0.1275602E-01 0.5832787E-04-0.1107698E-06 0.3072946E+05 0.2886431E+03
0.1000000E+01 0.9999999E+00-0.1097659E-02 0.2461455E-04 0.1000000E+01
0.1829893E-02-0.3191328E-04-0.1562498E-01 0.1427079E-03-0.5937434E-05
0.46E7498E-01-0.1998720E-03 0.7317495E-05
-0.9739065E+00-0.8650634E+00-0.6794096E+00-0.4333954E+00-0.1488743E+00
0.148E743E+00 0.4333954E+00 0.6794096E+00 0.8650634E+00 0.97390652E+00
0.6667134E-01 0.1494513E+00 0.2190864E+00 0.2692667E+00 0.2955242E+00
0.2955242E+00 0.2692667E+00 0.2190864E+00 0.1494513E+00 0.6667134E-01

C LISTING OF THE CCTPCT DATA FILE MAUTZ2.DAT

C

| N | NG | BK | VINC | |
|----------------|----------------|----------------|----------------|----------------|
| 36 | 10 | 0.1570796E+01 | 0.3141593E+01 | |
| X | | | | |
| 0.000000E+00 | 0.3026887E-01 | 0.8988691E-01 | 0.1770427E+00 | 0.2890879E+00 |
| 0.4226183E+00 | 0.5735764E+00 | 0.7373757E+00 | 0.9090390E+00 | 0.1083350E+01 |
| 0.1255014E+01 | 0.1418813E+01 | 0.1569771E+01 | 0.1703301E+01 | 0.1815347E+01 |
| 0.1902502E+01 | 0.1962121E+01 | 0.1992389E+01 | 0.1992389E+01 | 0.1962121E+01 |
| 0.1902502E+01 | 0.1815347E+01 | 0.1703301E+01 | 0.1569771E+01 | 0.1418813E+01 |
| 0.1255014E+01 | 0.1083350E+01 | 0.9090390E+00 | 0.7373757E+00 | 0.5735764E+00 |
| 0.4226183E+00 | 0.2890879E+00 | 0.1770427E+00 | 0.8988691E-01 | 0.3026887E-01 |
| 0.000000E+00 | | | | |
| Y | | | | |
| 0.8715574E-01 | 0.2588190E+00 | 0.4226183E+00 | 0.5735764E+00 | 0.7071068E+00 |
| 0.8191520E+00 | 0.9063078E+00 | 0.9659258E+00 | 0.9961947E+00 | 0.9961947E+00 |
| 0.9659258E+00 | 0.9063078E+00 | 0.8191520E+00 | 0.7071068E+00 | 0.5735764E+00 |
| 0.4226183E+00 | 0.2588190E+00 | 0.8715574E-01 | -0.8715574E-01 | -0.2588190E+00 |
| -0.4226183E+00 | -0.5735764E+00 | -0.7071068E+00 | -0.8191520E+00 | -0.9063078E+00 |
| -0.9659258E+00 | -0.9961947E+00 | -0.9961947E+00 | -0.9659258E+00 | -0.9063078E+00 |
| -0.8191520E+00 | -0.7071068E+00 | -0.5735764E+00 | -0.4226183E+00 | -0.2588190E+00 |
| -0.8715574E-01 | | | | |
| Z0 | | | | |
| -0.3072582E+04 | 0.7368758E+04 | -0.6085100E+03 | 0.1710234E+02 | -0.2271001E+00 |
| 0.1600171E-02 | -0.5961089E-05 | 0.9545773E-08 | 0.4163150E+05 | 0.3420211E+03 |
| 0.1000000E+01 | -0.6024727E+04 | 0.1613512E+04 | -0.7532210E+02 | 0.1402590E+01 |
| -0.1275602E-01 | 0.5832787E-04 | -0.1107698E-06 | 0.3072946E+05 | 0.2886431E+03 |
| 0.1000000E+01 | 0.9999999E+00 | -0.1097659E-02 | 0.2461455E-04 | 0.1000000E+01 |
| 0.1829893E-02 | -0.3191328E-04 | 0.1562498E-01 | 0.1427079E-03 | -0.5937434E-05 |
| 0.4687498E-01 | -0.1998720E-03 | 0.7317495E-05 | | |
| XG | | | | |
| -0.9739065E+00 | -0.8650634E+00 | -0.6794096E+00 | -0.4333954E+00 | -0.1488743E+00 |
| 0.1488743E+00 | 0.4333954E+00 | 0.6794096E+00 | 0.8650634E+00 | 0.9739065E+00 |
| AG | | | | |
| 0.6667134E-01 | 0.1494513E+00 | 0.2190864E+00 | 0.2692667E+00 | 0.2955242E+00 |
| 0.2955242E+00 | 0.2692667E+00 | 0.2190864E+00 | 0.1494513E+00 | 0.6667134E-01 |
| VINC | | | | |
| 0.1094818E+01 | -0.2603224E-01 | 0.1089960E+01 | -0.1031663E+00 | |
| 0.1070414E+01 | -0.2277548E+00 | 0.1021332E+01 | -0.3915596E+00 | |
| 0.9268360E+00 | -0.5797543E+00 | 0.7749375E+00 | -0.7703197E+00 | |
| 0.5626479E+00 | -0.9361391E+00 | 0.2993480E+00 | -0.1050082E+01 | |
| 0.6526236E-02 | -0.1091791E+01 | -0.2867749E+00 | -0.1053589E+01 | |
| -0.5514164E+00 | -0.9427966E+00 | -0.7656732E+00 | -0.7795281E+00 | |
| -0.9198373E+00 | -0.5907919E+00 | -0.1016581E+01 | -0.4037424E+00 | |
| -0.1067612E+01 | -0.2405345E+00 | -0.1088651E+01 | -0.1161893E+00 | |
| -0.1094428E+01 | -0.3911872E-01 | -0.1095153E+01 | -0.1309429E-01 | |
| -0.1094428E+01 | -0.3911890E-01 | -0.1088651E+01 | -0.1161897E+00 | |
| -0.1067612E+01 | -0.2405351E+00 | -0.1016581E+01 | -0.4037431E+00 | |
| -0.9198368E+00 | -0.5907926E+00 | -0.7656725E+00 | -0.7795288E+00 | |
| -0.5514155E+00 | -0.9427971E+00 | -0.2867739E+00 | -0.1053589E+01 | |
| 0.6527342E-02 | -0.1091791E+01 | 0.2993491E+00 | -0.1050081E+01 | |
| 0.5626488E+00 | -0.9361386E+00 | 0.7749382E+00 | -0.7703190E+00 | |
| 0.9268364E+00 | -0.5797535E+00 | 0.1021332E+01 | -0.3915590E+00 | |

0. 1070414E+01-0. 2277543E+00 0. 1089960E+01-0. 1031659E+00
 0. 1094818E+01-0. 2603204E-01 0. 1095231E+01 0. 0000000E+00

V A

0. 2994785E-01-0. 1381276E-02 0. 2858944E-01-0. 5333051E-02
 0. 2962683E-01-0. 1131610E-01 0. 2911258E-01-0. 1854561E-01
 0. 2649176E-01-0. 2613214E-01 0. 2176669E-01-0. 3322932E-01
 0. 1528127E-01-0. 3915687E-01 0. 7584020E-02-0. 4347779E-01
 -0. 6980846E-03-0. 4602249E-01-0. 8966518E-02-0. 4686616E-01
 -0. 1672587E-01-0. 4627063E-01-0. 2362260E-01-0. 4461700E-01
 -0. 2944913E-01-0. 4233324E-01-0. 3412371E-01-0. 3983858E-01
 -0. 3765389E-01-0. 3750189E-01-0. 4009859E-01-0. 3562038E-01
 -0. 4152818E-01-0. 3440646E-01-0. 4199799E-01-0. 3398786E-01
 -0. 4152818E-01-0. 3440646E-01-0. 4009859E-01-0. 3562038E-01
 -0. 3765389E-01-0. 3750189E-01-0. 3412371E-01-0. 3983858E-01
 -0. 2944913E-01-0. 4233324E-01-0. 2362260E-01-0. 4461700E-01
 -0. 1672587E-01-0. 4627063E-01-0. 8966518E-02-0. 4686616E-01
 -0. 6980846E-03-0. 4602249E-01 0. 7584020E-02-0. 4347779E-01
 0. 1528127E-01-0. 3915687E-01 0. 2176669E-01-0. 3322932E-01
 0. 2649176E-01-0. 2613214E-01 0. 2911258E-01-0. 1854561E-01
 0. 2962683E-01-0. 1131610E-01 0. 2858944E-01-0. 5333051E-02
 0. 2994785E-01-0. 1381276E-02 0. 0000000E+00 0. 0000000E+00

Z

0. 7473691E-01 0. 1385026E+00 0. 7335540E-01 0. 7065693E-01
 0. 6932754E-01 0. 2962639E-01 0. 6298721E-01 0. 6236447E-02
 0. 5483766E-01-0. 1027953E-01 0. 4548406E-01-0. 2216265E-01
 0. 3555794E-01-0. 3037457E-01 0. 2564739E-01-0. 3554059E-01
 0. 1624363E-01-0. 3820945E-01 0. 7709407E-02-0. 3891708E-01
 0. 2694717E-03-0. 3818308E-01-0. 5978546E-02-0. 3649254E-01
 -0. 1104134E-01-0. 3427249E-01-0. 1499958E-01-0. 3187981E-01
 -0. 1797623E-01-0. 2959581E-01-0. 2010926E-01-0. 2763171E-01
 -0. 2152729E-01-0. 2613496E-01-0. 2233387E-01-0. 2520174E-01
 -0. 2259513E-01-0. 2486496E-01-0. 2233394E-01-0. 2520178E-01
 -0. 2152726E-01-0. 2613493E-01-0. 2010927E-01-0. 2763173E-01
 -0. 1797624E-01-0. 2959584E-01-0. 1499953E-01-0. 3187969E-01
 -0. 1104136E-01-0. 3427249E-01-0. 5978571E-02-0. 3649271E-01
 0. 2694886E-03-0. 3818303E-01 0. 7709373E-02-0. 3891693E-01
 0. 1624367E-01-0. 3820957E-01 0. 2564739E-01-0. 3554058E-01
 0. 3555793E-01-0. 3037456E-01 0. 4548407E-01-0. 2216266E-01
 0. 5483765E-01-0. 1027953E-01 0. 6298724E-01 0. 6236455E-02
 0. 6932755E-01 0. 2962641E-01 0. 7335536E-01 0. 7065692E-01
 CA= 0. 2461616E+01 0. 4775566E+01, CP= 0. 1841846E-01 0. 3171688E+01
 CINC=-0. 2151464E+00

CUR1

0. 2113638E+01-0. 5360954E+00 0. 1598972E+01-0. 6872047E+00
 0. 1791495E+01-0. 9038445E+00 0. 1479588E+01-0. 1134857E+01
 0. 1068554E+01-0. 1316476E+01 0. 5917228E+00-0. 1386905E+01
 0. 1110202E+00-0. 1306445E+01-0. 2971143E+00-0. 1075142E+01
 -0. 5667900E+00-0. 7376537E+00-0. 6671781E+00-0. 3697278E+00
 -0. 6132755E+00-0. 5098838E-01-0. 4569358E+00 0. 1628754E+00
 -0. 2636858E+00 0. 2552014E+00-0. 8820872E-01 0. 2457596E+00
 0. 3996931E-01 0. 1756236E+00 0. 1167466E+00 0. 8950505E-01
 0. 1534665E+00 0. 2329606E-01 0. 1637747E+00-0. 1162453E-02
 0. 1534665E+00 0. 2329659E-01 0. 1167467E+00 0. 8950505E-01

0.3996842E-01 0.1756239E+00 -0.3820911E-01 0.2457597E+00
 -0.2636863E+00 0.2552012E+00 -0.4569371E+00 0.1628750E+00
 -0.6132758E+00 -0.5098913E-01 -0.6671781E+00 -0.3697297E+00
 -0.5667889E+00 -0.7376546E+00 -0.2971131E+00 -0.1075144E+01
 0.1110217E+00 -0.1306445E+01 0.5917245E+00 -0.1386905E+01
 0.1068555E+01 -0.1316475E+01 0.1479589E+01 -0.1134857E+01
 0.1791496E+01 -0.9038439E+00 0.1998973E+01 -0.6872036E+00
 0.2113638E+01 -0.5360951E+00 0.2149824E+01 -0.4822035E+00

CUBA

0.8435730E-01 -0.2000979E+00 0.7689659E-01 -0.7414376E-02
 0.6570814E-01 -0.4870010E-01 0.5236392E-01 -0.5136077E-01
 0.3856174E-01 -0.5534811E-01 0.2580129E-01 -0.5480544E-01
 0.1514947E-01 -0.5149234E-01 0.7139070E-02 -0.4639276E-01
 0.1799082E-02 -0.4062632E-01 -0.1219058E-02 -0.3507616E-01
 -0.2472905E-02 -0.3032159E-01 -0.2568123E-02 -0.2663050E-01
 -0.2039613E-02 -0.2401857E-01 -0.12E8466E-02 -0.2233653E-01
 -0.5694495E-03 -0.2135902E-01 -0.1499719E-04 -0.2085441E-01
 0.3240804E-03 -0.2063298E-01 0.4371095E-03 -0.2057321E-01
 0.3240795E-03 -0.2063297E-01 -0.1499475E-04 -0.2085441E-01
 -0.5694595E-03 -0.2135902E-01 -0.12E8466E-02 -0.2233653E-01
 -0.2039618E-02 -0.2401856E-01 -0.2568109E-02 -0.2663050E-01
 -0.2472912E-02 -0.3032158E-01 -0.1219056E-02 -0.3507617E-01
 0.1799082E-02 -0.4062631E-01 0.7139078E-02 -0.4639276E-01
 0.1514947E-01 -0.5149233E-01 0.2580127E-01 -0.5480543E-01
 0.3856175E-01 -0.5534811E-01 0.5236392E-01 -0.5136079E-01
 0.6570815E-01 -0.4870008E-01 0.7689659E-01 -0.7414370E-02
 0.8435730E-01 -0.2000979E+00 0.8697801E-01 0.3527458E+00
 YHS= 0.2771880E-01 -0.3082181E+01, YAB= 0.9196463E-01 -0.1235218E+02
 TI=-0.1835366E+01 0.4155412E+00, V=-0.3474545E-01 -0.1483277E+00
 YABH= 0.8403454E-01 -0.1077051E+02, VH=-0.3990850E-01 -0.1700951E+00

V. THE SUBROUTINE BESJ1

The subroutine BESJ1(N, X, BJ1) puts $J_1(I*X)$ in BJ1(I) for $I=1, 2, \dots, N$. Here, J_1 is the Bessel function of the first kind of order one, N is an integer not less than one, and X is a non-negative real number. The minimum allocation for BJ1 is given by

DIMENSION BJ1(N)

The subroutine BESJ1 is listed at the end of this section. If $I*X \leq 3$, then BJ1(I) is calculated by lines 7 to 20 inside DO loop 15 of the listing. As suggested in [2, Sec. 9.12., Example 1], $J_{MZ}(XX)$ and $J_{MZ-1}(XX)$ are set equal to the arbitrary values of zero and 10^{-20} , respectively, where

$$XX = I*X \quad (40)$$

and

$$MZ = 11 + 2[XX] \quad (41)$$

where $[XX]$ is the largest integer that does not exceed XX. This is done in lines 7 to 9. In DO loop 16, the recurrence relation (4) is used to calculate $\{J_n(XX), n = MZ-2, MZ-3, \dots, 0\}$. The calculated value of $J_1(XX)$ has to be divided by α of (5). This division is done in line 20.

If $I*X > 3$, then BJ1(I) is calculated by lines 22 to 32 inside DO loop 15. The polynomial approximation [2, eq. (9.4.6)] is used. With regard to [2, eq. (9.4.6)], lines 28 and 29 put f_1 in F, lines 30 and 31 put ϵ_1 in T, and line 32 puts $J_1(I*X)$ in BJ1(I).

```

C01C      LISTING OF THE SUBROUTINE BESJ1
C02      SUBROUTINE BESJ1(N,X,BJ1)
C03      DIMENSION BJ(18),BJ1(10000)
C04      DO 15 I=1,N
C05      XX=FLCAT(I)*X
C06      IF(XX-3.) 17,17,18
C07 17    MZ=11+2*IPIX(XX)
C08      BJ(MZ+1)=0.
C09      BJ(MZ)=1.E-20
C10      M1=MZ-1
C11      X2=2./XX
C12      DO 16 K=1,M1
C13      MK=MZ-K
C14      BJ(MK)=X2*FLOAT(MK)*BJ(MK+1)-BJ(MK+2)
C15 16    CONTINUE
C16      ALP=.5*BJ(1)
C17      DO 19 J=3,MZ,2
C18      ALP=ALP+BJ(J)
C19 19    CONTINUE
C20      BJ1(I)=BJ(2)/(2.*ALP)
C21      GO TO 15
C22 18    X1=3./XX
C23      X2=X1*X1
C24      X3=X2*X1
C25      X4=X3*X1
C26      X5=X4*X1
C27      X6=X5*X1
C28      F=-.7978846+.156E-05*X1+.1659667E-01*X2+.17105E-03*X3-
C29      1 .249511E-02*X4+.113653E-02*X5-.20033E-03*X6
C30      T=XX-2.356194+.1249961*X1+.565E-04*X2-.637879E-02*X3+
C31      1 .74348E-03*X4+.798242E-03*X5-.29166E-03*X6
C32      BJ1(I)=F/SQRT(XX)*CCS(T)
C33 15    CCNTINUE
C34      RETURN
C35      END

```

VI. THE SUBROUTINE BESJY

The subroutine BESJY(N1, N2, X, BJY) puts $J_N(X)$ $Y_N(X)$ in BJY(N) for $N=N1, N1+1, \dots, N2$ where J_N and Y_N are, respectively, the Bessel functions of the first and second kind of order N. Moreover, X is a non-negative real number, $N2 \geq N1$, and N1 is an integer appreciably larger than X so that Debye's asymptotic expansions [2, eqs. (9.3.7) and (9.3.8)] apply to $J_{N1}(X)$ and $Y_{N1}(X)$. The minimum allocation for BJY is given by

DIMENSION BJY(N2)

Combining [2, eqs. (9.3.7) to (9.3.9)], we obtain

$$J_N(X)Y_N(X) = -\frac{t}{N} \left(1 + \sum_{i=1}^4 \frac{u_i(t)}{N^i}\right) \left(1 + \sum_{i=1}^4 \frac{(-1)^i u_i(t)}{N^i}\right) \quad (42)$$

where

$$t = \frac{1}{\sqrt{1 - (X/N)^2}} \quad (43)$$

and

$$u_1(t) = (3t - 5t^3)/24 \quad (44)$$

$$u_2(t) = (81t^2 - 462t^4 + 385t^6)/1152 \quad (45)$$

$$u_3(t) = (30375t^3 - 369603t^5 + 765765t^7 - 425425t^9)/414720 \quad (46)$$

$$\begin{aligned} u_4(t) = & (4465125t^4 - 94121676t^6 + 349922430t^8 \\ & - 446185740t^{10} + 183910725t^{12})/39813120 \end{aligned} \quad (47)$$

Equation (43) is verified in the following manner. From [2, eq. (9.3.7)],

$$t = \coth x \quad (48)$$

Substituting

$$\operatorname{sech} \alpha = X/N \quad (49)$$

into the identity [2, eq. (4.5.17)]

$$\tanh \alpha = \sqrt{1 - \operatorname{sech}^2 \alpha} \quad (50)$$

and noting that $\coth \alpha$ is the reciprocal of $\tanh \alpha$, we obtain

$$\coth \alpha = \frac{1}{\sqrt{1 - (X/N)^2}} \quad (51)$$

Substitution of (51) into (48) gives the desired result (43).

The subroutine BESJY is listed at the end of this section. The right-hand side of (42) is calculated inside DO loop 11 of this listing. The order N that appears in (42) is obtained as the index of DO loop 11. Lines 5 to 8 put N , N^2 , N^3 , and N^4 in $F1$, $F2$, $F3$, and $F4$, respectively. With regard to (43)-(47), lines 10 to 20 put t^I in TI for $I=1,2,3,4,5,6,7,8,9,10,12$. Line 21 puts $u_1(t)/N$ in $U1$, line 22 puts $u_2(t)/N^2$ in $U2$, line 23 puts $u_3(t)/N^3$ in $U3$, and lines 24 and 25 put $u_4(t)/N^4$ in $U4$. Line 28 puts the right-hand side of (42) in $BJY(N)$.

```

001C      LISTING OF THE SUBROUTINE BESJY
C02      SUBROUTINE BESJY(N1,N2,X,BJY)
C03      DIMENSION BJY(10000)
C04      DO 11 N=N1,N2
C05          F1=N
C06          F2=F1*F1
C07          F3=F2*F1
C08          F4=F3*F1
C09          XN=X/F1
C10          T1=1./SQRT(1.-XN*XN)
C11          T2=T1*T1
C12          T3=T2*T1
C13          T4=T3*T1
C14          T5=T4*T1
C15          T6=T5*T1
C16          T7=T6*T1
C17          T8=T7*T1
C18          T9=T8*T1
C19          T10=T9*T1
C20          T12=T10*T2
C21          U1=(3.*T1-5.*T3)/(24.*F1)
C22          U2=(81.*T2-462.*T4+385.*T6)/(1152.*F2)
C23          U3=(30375.*T3-369603.*T5+765765.*T7-425425.*T9)/(414720.*F3)
C24          U4=(4465125.*T4-9412168.E+01*T6+3499224.E+02*T8-4461857.E+02*
C25          1 T10+1859107.E+02*T12)/(3981312.E+01*F4)
C26          U5=1.+U2+U4
C27          U6=U1+U3
C28          BJY(N)=-T1/(3.141593*F1)*(U5+U6)*(U5-U6)
C29 11      CONTINUE
C30      RETURN
C31      END

```

VII. THE MAIN PROGRAM FOR THE FOURIER SERIES METHOD OF SOLUTION

The main program for the Fourier series method of solution calculates the complex constant V of [1, eq. (B-25)]. Input data are read from the file MAUTZ3.DAT, output data are written on the file MAUTZ4.DAT, and the subroutines BES, BESJ1, and BESJY are called. These subroutines are described in Sections II, V, and VI.

The main program for the Fourier series method of solution is listed at the end of this section. In the open statements on lines 6 and 7 of this listing, MAUTZ3.DAT is the input data file and MAUTZ4.DAT is the output data file. The input data are read early in the program according to

```

      READ(20,17) N1, N2, X, P
      17   FORMAT(I3, I5, 2E14.7)
      READ(20,11)(YO(I), I = 1, 33)
      11   FORMAT(5E14.7)
    
```

The definitions of $N1$ and $N2$ are based on the technical digression in the next paragraph.

Truncating the infinite series in [1, eq. (B-25)], we obtain

$$V = -\frac{2}{\phi_o} \frac{U_1}{U_2} e^{-jka \cos \phi_o} \quad (52)$$

where

$$U_1 = \frac{1}{4H_o^{(2)}(ka)} + \sum_{N=1}^{N1-1} \frac{j}{H_N^{(2)}(ka)} \left(\frac{J_1(N\phi_o)}{N\phi_o}\right)^2 \quad (53)$$

and

$$\begin{aligned}
 U_2 = & \frac{1}{8J_o(ka)H_o^{(2)}(ka)} + \sum_{N=1}^{N1-1} \frac{1}{J_N(ka)H_N^{(2)}(ka)} \left(\frac{J_1(N\phi_o)}{N\phi_o}\right)^2 \\
 & + j \sum_{N=N1}^{N2} \frac{1}{J_N(ka)Y_N(ka)} \left(\frac{J_1(N\phi_o)}{N\phi_o}\right)^2
 \end{aligned} \quad (54)$$

In (53) and (54), $H_N^{(2)}$ is the Hankel function of the second kind of order N. According to (23),

$$H_N^{(2)}(ka) = J_N(ka) - jY_N(ka) \quad (55)$$

where J_N and Y_N are, respectively, the Bessel functions of the first and second kinds of order N. Still in (53) and (54), N1 and N2 are positive integers such that

$$N2 \geq N1 \quad (56)$$

$$N1 \gg ka \quad (57)$$

$$N2 \gg \pi/\phi_0 \quad (58)$$

The inequality (57) allows the series in (53) to be truncated at $N=N1-1$. It allows deletion of the quantity $J_N(ka)$ on the right-hand side of (55) whenever $N \geq N1$, so that $j/Y_N(ka)$ instead of $1/H_N^{(2)}(ka)$ could be put in the second summation on the right-hand side of (54). The inequality (58) is necessary because, in order for [1, eq. (B-9)] to be well-satisfied, $e^{jm\phi}$ terms whose periods are appreciably smaller than $2\phi_0$ must be retained on the left-hand side of [1, eq. (B-9)]. The period of $e^{jm\phi}$ is $2\phi_0$ when m is π/ϕ_0 .

The N1 and N2 that appear in the first read statement are the same as those in (53) and (54). In the same read statement, X is the electrical length ka in (53) and (54), and P is the angle ϕ_0 in (53) and (54). Here, P is in radians. In the second read statement, the array Y0 contains input data for the subroutine BES. The values of the elements of Y0 were given in Section II. These values should not deeply concern the user because he will never have to change them.

Minimum allocations are given by

```
COMMON BJ(N1), BY(N1)
DIMENSION BJ1(N2), BJV(N2)
```

Immediately after the main program at the end of this section, the contents of the input data file MAUTZ3.DAT and the output data file MAUTZ4.DAT are listed when

$$\left. \begin{array}{l} N1 = 20 \\ N2 = 10000 \\ X = \pi/2 \\ P = \pi/36 \end{array} \right\} \quad (59)$$

The values of X and P in (59) obtain the example of [1, Section VIII]. These values mean that

$$ka = \pi/2 \quad (60)$$

and

$$\pi/\beta_0 = 36 \quad (61)$$

In view of (60) and (61), the values of N1 and N2 in (59) satisfy the inequalities (57) and (58). The output data file MAUTZ4.DAT contains all the data put out by the write statements in the main program for the Fourier series method of solution. The contents of the output data file MAUTZ4.DAT are described in the next three paragraphs.

The input data are written out immediately after they are read in. The jth number in the ith row under the heading "BJ" is $J_{5(i-1)+j-1}(ka)$. The jth number in the ith row under the heading "BY" is $Y_{5(i-1)+j-1}(ka)$. By means of (55), the Bessel functions mentioned in the previous two sentences are used to construct the $H_0^{(2)}(ka)$ and the $H_N^{(2)}(ka)$ that appear

in (53). The number preceded by "BJ1(1)=" is $J_1(\frac{N}{\phi})$, and the number preceded by "BJ1(N2)=" is $J_1(N2\frac{\phi}{\phi})$.

Each line under the heading "N U1 U2" contains five numbers. The second and third numbers are the real and imaginary parts of the right-hand side of (53) with N1-1 replaced by the first number. The fourth and fifth numbers are the real and imaginary parts of the right-hand side of (54) with the maximum value of N therein equal to the first number.

The number preceded by "BJY(N1)=" is $J_{N1}(ka)Y_{N1}(ka)$, and the number preceded by "BJY(N2)=" is $J_{N2}(ka)Y_{N2}(ka)$. The numbers written under the heading "BJ1" are

$$\sum_{N=N1}^{N2} \frac{1}{J_N(ka) Y_N(ka)} \left(\frac{J_1(N\frac{\phi}{\phi})}{N\phi} \right)^2 \quad (62)$$

where I runs from N1 to N2 in steps of 50. These numbers are written in order to observe the rate at which (62) converges as I increases. Finally, the two numbers preceded by "V=" are, respectively, the real and imaginary parts of V of (52).

Lines 17 to 19 define the common variables (2) that are input data for the subroutine BES. Line 21 puts $J_N(ka)$ in BJ(N+1) for $N=0,1,\dots,N1-1$. Line 21 also puts $Y_N(ka)$ in BY(N+1) for $N=0,1,\dots,N1-1$. Line 26 puts $J_1(N\frac{\phi}{\phi})$ in BJ1(N) for $N=1,2,\dots,N2$.

Line 30 puts in U1 the term not governed by the summation sign in (53). Line 31 puts in U2 the term not governed by either one of the summation signs in (54). Inside DO loop 13, line 47 adds to U1 the term whose summation index is N in (53), and line 48 adds to U2 the term whose summation index is N in (54). Line 39 puts $\left(\frac{J_1(N\frac{\phi}{\phi})}{N\phi} \right)$ in B. Line 41 puts $J_N(ka)$ in

BJN. Lines 42 to 45 put $(\frac{J_1(N\phi_o)}{N\phi_o})/H_N^{(2)}(ka)$ in U3. If $|J_N(ka)| \leq 10^{-10}$, then, as a measure to avoid an underflow, $H_N^{(2)}(ka)$ is approximated by $-jY_N(ka)$. After line 46 is executed, j^N will reside in U.

Line 51 puts $J_N(ka) Y_N(ka)$ in BRY(N) for $N=N1, N1+1, \dots, N2$. Inside DO loop 14, line 58 accumulates in S the second summation on the right-hand side of (54). The index N of DO loop 14 obtains the summation index N of (54). Line 57 puts $(\frac{1}{N\phi_o})$ in B. Line 63 puts the right-hand side of (54) in U2. Finally, line 65 puts V of (52) in V.

Our description of the main program for the Fourier series method of solution is summarized in Table 3 where key variables in this program are listed. Each variable is identified by the line where it was read in, defined, or incremented, and by its corresponding quantity in the text.

Table 3. Key variables in the computer program, program lines where they are read in, defined, or incremented, and their corresponding quantities in the text.

| Program variables | Program line | Corresponding quantity in the text | Equation(s) where the quantity appears |
|-------------------|--------------|--|--|
| N1 | 8 | N1 | (53)-(54) |
| N2 | 8 | N2 | (54) |
| X | 8 | ka | (52)-(55) |
| P | 8 | ϕ_o | (52)-(54) |
| YO | 12 | P0m and Q0m | (7), (9), (12), (15), (14), (16) |
| BJ(N+1) | 21 | $J_N(ka)$ | (53)-(55) |
| BY(N+1) | 21 | $Y_N(ka)$ | (53)-(55) |
| BJ1(N) | 26 | $J_1(N\phi_o)$ | (53)-(54) |
| U1 | 30 | $1/(4H_o^{(2)}(ka))$ | (53) |
| U2 | 31 | $1/(8J_o(ka)H_o^{(2)}(ka))$ | (54) |
| B | 39 | $\frac{J_1(N\phi_o)}{N\phi_o}$ | (53)-(54) |
| BJN | 41 | $J_N(ka)$ | (53)-(55) |
| U3 | 42-45 | $(\frac{J_1(N\phi_o)}{N\phi_o})/H_N^{(2)}(ka)$ | (53)-(54) |
| U | 46 | j^N | (53) |
| U1 | 47 | U1 | (53) |
| U2 | 48 | U2 without $j \sum_{N=N1}^{N2}$ | (54) |
| BJY(N) | 51 | $J_N(ka)Y_N(ka)$ | (54) |
| B | 57 | $J_1(N\phi_o)/N\phi_o$ | (54) |
| S | 58 | $\sum_{N=N1}^{N2}$ | (54) |
| U2 | 63 | U2 | (54) |
| V | 65 | V | (52) |

```

C01C      LISTING OF THE MAIN PROGRAM FOR THE
002C      FOURIER SERIES METHOD OF SOLUTION
C03      COMPLEX U1,U2,U,J3,V
C04      COMMNC Y0(33),PI2,PI4,PI7,BJ(100),BY(100)
C05      DIMENSION BJ1(10000),BJY(10000)
C06      OPEN(UNIT=20,FILE='MAUT23.DAT')
C07      OPEN(UNIT=21,FILE='MAUT24.DAT')
C08      READ(20,17) N1,N2,X,P
C09 17    FCRRMAT(I3,I5,2E14.7)
C10      WRITE(21,27) N1,N2,X,P
C1127   FORMAT(' N1=',I3,', N2=',I5,', X=',E14.7,', P=',E14.7)
C12      READ(20,11) (Y0(I),I=1,33)
C13 11   FCRRMAT(5E14.7)
C14      WRITE(21,12) (Y0(I),I=1,33)
C15 12   FCRRMAT(' Y0'/(1X,5E14.7))
C16      PI=3.141593
C17      PI2=2./PI
C18      EI4=PI/4.
C19      PI7=.75*PI
C20      N1M=N1-1
C21      CALL BES(N1M,X)
C22      WRITE(21,18) (BJ(I),I=1,N1)
C23 18   FCRRMAT(' BJ'/(1X,5E14.7))
C24      WRITE(21,19) (BY(I),I=1,N1)
C25 19   FORMAT(' BY'/(1X,5E14.7))
C26      CALL BESJ1(N2,P,EJ1)
C27      WRITE(21,20) BJ1(1),BJ1(N2)
C28 20   FCRRMAT(' BJ1(1)=',E14.7,', EJ1(N2)=',E14.7)
C29      N=0
C30      U1=-.25/CMPLX(BJ(1),-BY(1))
C31      U2=-.5/BJ(1)*U1
C32      WRITE(21,15)
C33 15   FORMAT(' N',14X,'U1',26X,'U2')
C34      WRITE(21,25) N,U1,U2
C35 25   FORMAT(1X,I3,4E14.7)
C36      U=(1.,0.)
C37      DO 13 N=1,N1M
C38      FN=N*P
C39      B=BJ1(N)/FN
C40      NP=N+1
C41      EJN=BJ(NP)
C42      IP(ABS(EJN)-1,2-10) 22,22,23
C43 22   U3=B/BY(NP)*(0.,1.)
C44      GO TO 24
C45 23   U3=B/CMPLX(EJN,-BY(NP))
C46 24   U=U*(0.,1.)
C47      U1=U*U3+U1
C48      U2=B/EJN*U3+U2
C49      WRITE(21,25) N,U1,U2
C50 13   CCNTINUE
C51      CALL BESJY(N1,N2,X,EJY)
C52      WRITE(21,21) BJY(N1),BJY(N2)
C53 21   FORMAT(' BJY(N1)=',E14.7,', BJY(N2)=',E14.7)

```

```

054      S=0.
055      DO 14 N=N1,N2
056      FN=N*P
057      E=BJ1(N)/FN
058      S=S+E*B/BJY(N)
059      EJ1(N)=S
060 14    CONTINUE
061      WRITE(21,16) (BJ1(I),I=N1,N2,50)
062 16    FORMAT(' BJ1'/(1X,6E11.4))
063      U2=S*(0.,1.)*J2
064      S=X*COS(P)
065      V=-2./P*U1/U2*CMPLX(COS(S),-SIN(S))
066      WRITE(21,26) V
067 26    FCRMAT(' V=' ,2E14.7)
068      STOP
069      END

```

C LISTING OF THE INPUT DATA FILE MAUTZ3.DAT

```

C
2010000 0.1570796E+01 0.8726646E-01
-0.3072582E+04 0.7368758E+04-0.6085100E+03 0.1710234E+02-0.2271001E+00
0.1600171E-02-0.5961089E-05 0.9545773E-08 0.4163150E+05 0.3420211E+03
0.1000000E+01-0.6024727E+04 0.1613512E+04-0.7532210E+02 0.1402590E+01
-0.1275602E-01 0.5832787E-04-0.1107698E-06 0.3072946E+05 0.2886431E+03
0.1000000E+01 0.9999999E+00-0.1097659E-02 0.2461455E-04 0.1000000E+01
0.1829893E-02-0.3191328E-04-0.1562498E-01 0.1427079E-03-0.5937434E-05
0.4687498E-01-0.1998720E-03 0.7317495E-05

```

C LISTING OF THE CCTPUT DATA FILE MAUTZ4.DAT

C N1= 20, N2=10000, X= 0.1570796E+01, P= 0.8726646E-01

Y0

-0.3072582E+04 0.7368758E+04-0.6085100E+03 0.1710234E+02-0.2271001E+00
 0.1600171E-02-0.5961089E-05 0.9545773E-08 0.4163150E+05 0.3420211E+03
 0.1000000E+01-0.6024727E+04 0.1613512E+04-0.7532210E+02 0.1402590E+01
 -0.12756C2E-01 0.5832787E-04-0.1107698E-06 0.3072946E+05 0.2886431E+03
 0.1000000E+01 0.9999999E+00-0.1097659E-02 0.2461455E-04 0.1000000E+01
 0.1829853E-02-0.3191328E-04-0.1562498E-01 0.1427079E-03-0.5937434E-05
 0.4687498E-01-0.1998720E-03 0.7317495E-05

BJ

0.4720014E+00 0.5668241E+00 0.2497016E+00 0.6903585E-01 0.1399603E-01
 0.2245355E-02 0.2983472E-03 0.3385059E-04 0.3352192E-05 0.2945642E-06
 0.2326610E-07 0.1669C26E-08 0.1096726E-09 0.6648497E-11 0.3740814E-12
 0.1963744E-13 0.9661458E-15 0.4472615E-16 0.1955078E-17 0.8094814E-19

BY

0.4100035E+00-0.3662806E+00-0.8763665E+00-0.1865369E+01-0.6248819E+01
 -0.2995961E+02-0.1844800E+03-0.1379364E+04-0.1210935E+05-0.1219655E+06
 -0.1385513E+07-0.1751893E+08-0.2439783E+09-0.3710196E+10-0.6116762E+11
 -0.1086625E+13-0.2069184E+14-0.4204441E+15-0.9079853E+16-0.2076745E+18

BJ1(1)= 0.4359171E-01, BJ1(N2)=-0.2690578E-01

| N | U1 | U2 |
|----|---------------|---|
| 0 | 0.3018775E+00 | 0.2622256E+00 0.3197845E+00 0.2777805E+00 |
| 1 | 0.7036024E+00 | 0.8839002E+00 0.8676468E+00-0.7624704E-01 |
| 2 | 0.5538185E+00 | 0.1409590E+01 0.1166432E+01-0.1124881E+01 |
| 3 | 0.2884284E+00 | 0.1399768E+01 0.1236961E+01-0.3030578E+01 |
| 4 | 0.2886049E+00 | 0.1320966E+01 0.1243170E+01-0.5803081E+01 |
| 5 | 0.3049000E+00 | 0.1320967E+01 0.1243436E+01-0.9346033E+01 |
| 6 | 0.3049000E+00 | 0.1323586E+01 0.1243443E+01-0.1358569E+02 |
| 7 | 0.3045541E+00 | 0.1323586E+01 0.1243443E+01-0.1845940E+02 |
| 8 | 0.3045541E+00 | 0.1323547E+01 0.1243443E+01-0.2390473E+02 |
| 9 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.2985677E+02 |
| 10 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.3624775E+02 |
| 11 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.4300740E+02 |
| 12 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.5006366E+02 |
| 13 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.5734352E+02 |
| 14 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.6477395E+02 |
| 15 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.7228288E+02 |
| 16 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.7980009E+02 |
| 17 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.8725819E+02 |
| 18 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.9459342E+02 |
| 19 | 0.3045579E+00 | 0.1323547E+01 0.1243443E+01-0.1017465E+03 |


BJY(N1)=-0.1596493E-01, BJY(N2)=-0.3183099E-04

EJ1

-0.6917E+01-0.8147E+02-0.8840E+02-0.9237E+02-0.9453E+02-0.9555E+02
 -0.9661E+02-0.9716E+02-0.9763E+02-0.9807E+02-0.9831E+02-0.9861E+02
 -0.9881E+02-0.9898E+02-0.9916E+02-0.9927E+02-0.9940E+02-0.9951E+02
 -0.9959E+02-0.9969E+02-0.9975E+02-0.9983E+02-0.9990E+02-0.9994E+02
 -0.1000E+03-0.1000E+03-0.1001E+03-0.1001E+03-0.1002E+03-0.1002E+03
 -0.1002E+03-0.1003E+03-0.1003E+03-0.1003E+03-0.1004E+03-0.1004E+03
 -0.1004E+03-0.1004E+03-0.1004E+03-0.1005E+03-0.1005E+03-0.1005E+03
 -0.1005E+03-0.1005E+03-0.1006E+03-0.1006E+03-0.1006E+03-0.1006E+03

REFERENCES

- [1] J. R. Mautz, X. Yuan, and R. F. Harrington, "Electromagnetic Scattering from a Slotted TM Cylindrical Conductor by the Pseudo-Image Method," Technical Report SYRU/DECE/TR-85/3, Department of Electrical and Computer Engineering, Syracuse University, Syracuse, NY 13210, Sept. 1985.
- [2] M. Abramowitz and I. A. Stegun, Handbook of Mathematical Functions, U. S. Government Printing Office, Washington, D.C. (Natl. Bur. Std. U.S. Applied Math. Ser. 55), 1964.
- [3] J. F. Hart et al., Computer Approximations, Wiley, New York, 1968.
- [4] J. R. Mautz and R. F. Harrington, "Transmission from a Rectangular Waveguide into Half Space through a Rectangular Aperture," Technical Report TR-76-5, Department of Electrical and Computer Engineering, Syracuse University, Syracuse, NY 13210, May 1976.
- [5] V. I. Krylov, Approximate Calculation of Integrals, Macmillan, New York, 1962.



A hand-drawn signature or code in black ink. It consists of four main strokes: a large circle on the left, a vertical stroke in the center, a diagonal stroke to the right, and a smaller circle on the far right.

A hand-drawn number in black ink. It features a large '7' on the left, followed by a short horizontal line, and a large '86' on the right.